

FDP - A8/16

FIBRE DISTRIBUTION POINT AERIAL

APPLICATION

The FDP A closure is specifically designed for overhead and wall applications:

FEATURES

- Mechanical sealing mechanism of the closure allows for easier installation and re-entry
- Minimum tools are required on installation and re-entry
- The FDP - A is designed with additional safety in the open & close clamping system ie. Aerial application
- The FDP - A lid is self-supportive when in an open position there is no need for a support bar
- The connector tray is optional, it has a SC/LC Duplex footprint
- The PLC Splitter housing sits at the back of the connector tray. Suitable for 1:8 or 1:16 way splitter
- IP65 rating



SPECIFICATION

| AVT No. | Size(mm) L x W x H | Connector Tray | Cable Ports | Max. Splice Tray Capacity | Max. Diameter of cable (mm) |
|---------|-----------------------|-------------------|--|--|---|
| FDP-A8 | 305 x 216 x 107 | FDP -A8 8 x SC | 2 x Oval Uncut 4 x Branch 8 x Drop Max 4 Splice trays with Connector tray | 6 Trays Splice only FDP - 12F Tray = 72F FDP - 24F Tray = 144F | 2 x Oval port 11.5 - 15.5mm 4 x Branch port 9 - 12mm 2 x Drop 2.5 - 3.5mm 2 x Drop 3.5 - 5mm |

| AVT No. | Size(mm) L x W x H | Connector Tray | Cable Ports | Max. Splice Tray Capacity | Max. Diameter of cable (mm) |
|---------|-----------------------|---------------------|--|--|--|
| FDP-A16 | 305 x 216 x 107 | FDP -A16 16 x SC | 2 x Oval Uncut 16 x Drops Max 4 Splice trays with Connector tray | 6 Trays Splice only FDP - 12F Tray = 72F FDP - 24F Tray = 144F | 2 x Oval port 11.5 - 15.5mm 16 x Drop ports 3.5 - 5mm |

PRODUCT IMAGES



FDP - A16

FDP - A8

