

ODC FD08L

OPTICAL DISTRIBUTION CLOSURE

APPLICATION

The closure represents the following range of applications:

- Telecommunications Networks
- FTTH Networks
- Small and compact , ideal for boundary box solutions
- Outdoor applications

FEATURES

- Maximum splice capacity is 24F
- Up to 8 drop cables underground, 16 drop cables overhead
- Up to 8 Adapter: SC/LC Duplex adaptors
- The oval port is for 1 loop cable or 2 cables with max \varnothing 8 mm or \varnothing 5 mm
- The closure can accommodate 8 drop cables \varnothing 2 - 6 mm.
- Can accommodate 1x4 or 1x8 PLC splitter
- Design for small manholes/ boundary boxes
- Re-enterable
- Cable fixation on the inside and outside of the closure to secure Loop and Drop cables
- IP68 , gel sealing
- ROHS compliance



SPECIFICATION

Dimensions(mm)	ODC - FD08L
Length	223mm
Width	161mm
Height	73mm
Splice Tray	Fibre Splicing Capacity
Single Tray Splicing	24 splices
Accessibility	Cable Dimensions
Access Ports Fibre Optic Cable	2 Ports: Round 8mm
Access Ports Drop Fibre Cable	8 Ports: Round 2-6mm

PRODUCT IMAGES

