

ODB-O OPTICAL DISTRIBUTION BOX-O

APPLICATION

The box represents the following range of applications :

- Telecommunications
- FTTH Networks
- CATV Networks
- Local Area Networks
- Data Communications Networks
- Indoor and Outdoor IP65 applications

FEATURES

- Indoor and outdoor use
- Designed for Wall and Pole mount applications
- Safety lock
- Available for SC/LC adapters (up to 16 Simplex SC adapters)
- IP 65
- Accepts loose tube, distribution cables
- Bend radius protection
- Rugged and durable construction for long term reliability (UV resistance)
- Resistance to vibration and shock
- Door with secure mechanism
- Can accommodate up to 1 piece of 1 x 8 or 1 x 16 PLC Splitter
- Up to 16 drop cables
- Design for small and medium volumes of fibre optic cables
- Whole front operation
- Convenient for expansion of capacity
- Reusable



SPECIFICATION ODB-O

Dimension	ODB-O
Length	320 mm
Width	260 mm
Depth	90 mm
Splice	Fibre Splicing Capacity
Single Tray Splicing	1 trays (16 splices)
Accessible	Cable
Access Ports Fibre Optic Cable	2 Ports > 12 mm
Access Ports Drop Fibre Cable	16 Ports > 3.5 mm

DIMENSIONS

